


## Practicus floor drain press.seal. DN 70, horizontal, Slotted grating





## Article information

Item no.: 45179.11 GTIN: 4026092033029

Price group: 10

## **Advantages**

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

## **Description**

The Practicus polymer floor drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

Variant

System: 125

Waterproofing layer on the upper section: Connection flange

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

Sealing water height: 50 mm Discharge rate (l/s) with 20 mm backwater: 1,3

General characteristics

Standard: EN 1253-1 Nominal size (DN): 70 Outer diameter (OD): 75 mm

**Dimensions** 



Net weight: 1,94 kg Gross weight: 2,57 kg

Vertical adjustment: vertically adjustable upper section

Length:273 mmWidth:273 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1
Material of drain body: PP
System: lateral

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 138 mm
Height of cover: 16 mm
Length of cover: 138 mm
Frame material: ABS
Cover locking: screwed

Load class: K 3 (EN 1253-1)

Grating colour: Kessel
Rim length: 150 mm
Rim material: 150 mm

Upper section: vertically adjustable

Upper section material: ABS
Odour trap: included